


FOR ARRIS MODEM



Step 1:

Open your google chrome app. Type **192.168.0.1** on the URL bar.



Step 2:

Log in your modem using the username: **admin** and password: **password**



This Web based Manager for your Gateway allows you to configure and control your Gateway, providing assistance with basic troubleshooting.

Login

Please enter username and password to login.

Username	<input type="text" value="admin"/>
Password	<input type="password" value="*****"/>
<input type="button" value="Login"/>	

For information regarding software licenses, acknowledgments and copyright notices for certain software packages and/or components that are used in this SBG6580-2, please see the [Open Source Software Information](#).



Step 3:

On the top side of the screen click **Wireless** then **Primary Network Settings**



Step 4:

You can change the name of your wifi network by changing the name in the **Network Name (SSID)** box.

You can change the password of your wifi network by changing the name in the **Passphrase** box.

Click on the **Apply** when you're done.

Wireless - Primary Network Settings

Configure your wireless network. You can use a wireless local area network (WLAN) to share Internet access, files, printers, game consoles, and other devices among all the devices in your home.

Wi-Fi Network		
SC:E3:0E:E3:4E:7B		
Wireless Network	<input checked="" type="radio"/> Enabled <input type="radio"/> Disabled	▶ Help
Network Name (SSID)	<input type="text" value="SBG6580-2-6E2FD"/>	▶ Help
Network Name (SSID) Broadcast	<input checked="" type="radio"/> Enabled <input type="radio"/> Disabled	▶ Help
AP Isolate	<input type="text" value="Disabled"/>	▶ Help
Wireless Security	<input type="text" value="WPA2-PSK"/>	▶ Help
WPA2-PSK Security Settings		
Encryption	<input checked="" type="radio"/> AES <input type="radio"/> AES+TKIP	▶ Help
Passphrase	<input type="text" value="nctv2000"/>	▶ Help
Wi-Fi Protected Setup (WPS) Automatic Security Configuration		
WPS	<input checked="" type="radio"/> Enabled <input type="radio"/> Disabled	▶ Help
WPS PIN Methods	<input type="radio"/> Enabled <input checked="" type="radio"/> Disabled	▶ Help
WPS Add Client (Push Button Method)	Press the button on the SBG6580-2 to start WPS pairing.	▶ Help
Configure by External Registrar	<input type="text" value="Allow"/>	▶ Help
<input type="button" value="Apply"/> <input type="button" value="Cancel"/>		